







## System Description

# System Hitch Control



---

<b>System Description</b>	<b>Hitch Control</b>
---------------------------	----------------------

---

**Revision history***Table of revisions*

Date	Changed	Rev
August 2015	Converted to Danfoss layout	BA
December 2008		AA

---

## System Description      Hitch Control

---

### Contents

#### Overview

About this document.....	4
Referenced product specific documents.....	4
Microcontroller.....	4
Valves.....	4
Software.....	4
System start-up procedures.....	4
Latest version of technical literature.....	4
PLUS+1® electronic controls responsibility.....	4
Hitch positioning control concepts.....	4

#### System details

Closed loop work control modes.....	6
Combination of position, force and slip control.....	6
Adaptive force control.....	6
Fast down control.....	6
In-cab control from HMI.....	6
Remote operation.....	7
Closed loop transport modes.....	7
Rear hitch active damping.....	7
Front hitch active damping.....	7

#### Control options

Overview.....	8
PVBZ double-acting actuator control.....	8
PVBZ-HS single-acting actuator control.....	8
PVBZ-HD single and double-acting actuator control.....	9

#### Hardware components

Hitch valves.....	10
Sensors.....	10
Draft sensors for force control.....	10
Angle sensor for displacement control.....	10
Ground speed radar.....	10
Microcontrollers.....	10
PLUS+1® controller power supply specification.....	10
MC024-01A controller for 10 Vdc draft sensors.....	10
HWD for PLUS+1® controllers.....	10

#### Application software

Application block software description.....	11
PLUS+1® GUIDE.....	11
PLUS+1® Service Tool.....	11
PLUS+1® Service Tool functions.....	11
Keyed PLUS+1® application block software and application hardware.....	11
Customer access to the Hitch application block.....	11
Application file contents.....	11
Application file download and installation in GUIDE.....	11

#### Features and benefits

Standard features.....	12
Optional features.....	12
Benefits.....	12

---

## System Description      Hitch Control

---

### Overview

### About this document

This document provides general information about the PLUS+1® Hitch Control System application block. In addition, it is a reference tool for vehicle OEM design, engineering, and service personnel.

This document is one of several sources of technical information for the hitch control system. Other sources of technical information include individual product data sheets and application block manuals, *PLUS+1® GUIDE User Manual*, and *PLUS+1® Service Tool User Manual*.

### Referenced product specific documents

#### Microcontroller

- *PLUS+1® Controller Family Technical Information*, **520L0719**
- *PLUS+1® MC024-01A Controller Data Sheet*, **11030820**

#### Valves

- *PVG Proportional Valves Brochure*, **520L0690**
- *PVG 32 Proportional Valves Technical Information*, **520L0344**
- *Basic Module Type PVBZ Valve (hitch double-acting) Data Sheet*, **520L0681**
- *Basic Module Type PVBZ-HS Valve (hitch single-acting) Data Sheet*, **520L0956**
- *Basic Module Type PVBZ-HD Valve (hitch double-acting) Data Sheet*, **11035599**

#### Software

- *PLUS+1® GUIDE Data Sheet*, **520L0708**
- *PLUS+1® GUIDE User Manual*, **10100824**
- *PLUS+1® Service Tool User Manual*, **520L0899**
- *Hitch Control Application Block User Manual*, **11033753**

#### System start-up procedures

- *Recommended System Start-up Procedures Technical Information*, **11010667**

#### Latest version of technical literature

---

Danfoss product literature is online at: <http://powersolutions.danfoss.com/literature/>

---

### PLUS+1® electronic controls responsibility

The manufacturer of a machine or vehicle using PLUS+1® electronic controls is responsible for correctly applying and programming GUIDE-programmable PLUS+1® products. Danfoss strongly recommends that the OEM perform a system-level Failure Mode Effects Analysis (FMEA).

You can find additional information about OEM responsibilities in the:

- *PLUS+1® Controller Family Technical Information*, **520L0719**
- *Recommended System Start-up Procedures Technical Information*, **11010667**

### Hitch positioning control concepts

The purpose of the hitch control system is to allow the operator to position the hitch linkage either in a work or transport position. Set points for transport and work are adjustable parameters. A closed loop position control compares the set-point to the actual input from the position sensor. If there is a difference, it controls the valve to lower or raise the linkage.


## System Description      Hitch Control

### Overview

The goal of an automated hitch control system is to:

- Facilitate fast and easy attachment of implements to the tractor
- Optimize the tractor implement output during field operation as measured in acres/hour or fuel consumption/acres relative to manually controlled systems
- Provide a safer and more comfortable transport of the implement between field operations

*Typical rear hitch*



3513

## System Description Hitch Control

### System details

#### Closed loop work control modes

When the operator chooses work control mode, the position control adjusts the linkage to the depth reference set point.


#### Combination of position, force and slip control

In work position it is not always possible for the tractor to do the job with the specified set point. Therefore different sensors in the system collect information about the pull force and the wheel slip.

The system compares these inputs with an operator defined preset maximum value. If the current pull force or wheel slip are higher than the preset maximum value, it calculates a delta and adds to the set point for the work position.

When the set point is increased, the pull force/wheel slip decreases, and causes recalculation of the delta. In this way, the system continually modulates the linkage position according to the sensor inputs.

#### Combined position, force and slip control



3514

#### Adaptive force control

It is sometimes difficult for the operator to find the correct parameter settings for force control in some work situations. Selecting adaptive force control allows the system to automatically adjust to changing field conditions.

#### Fast down control

This mode gets the implement more quickly to the correct working depth.

- Single acting: This mode bypasses the closed loop control and sends the valve to maximum lowering.

Maximum lowering is still subject to scale function according to implement weight, to avoid hazardous lowering speeds.

- Double acting: This mode maintains the closed loop control. The only difference to work mode is that the digital output to switch between single and double acting, is set for double acting operation.

#### In-cab control from HMI

You can expand the Human Machine Interface (HMI) with up/down buttons or a joystick for manual operation. In manual operation the operator gives direct input to the valve. This is very useful for attaching and detaching implements.

---

**System Description****Hitch Control**

---

**System details**

- Analog joystick: Control of the valve is proportional from zero to the specified maximum value.
- Digital buttons: If the application uses on/off buttons, pressing the appropriate button sets the valve to the specified maximum value.

**Remote operation**

It is possible to operate the hitch valve with buttons outside the cab. This operation overrides any other mode, and leaves the system in safe state after operation. When back in the cab, the operator must choose desired mode.

**Closed loop transport modes**

In transport mode, the position control adjusts the linkage to the upper limit set point.

**Rear hitch active damping**

When traveling with a heavy implement lifted, the tractor can start to oscillate around the rear axle. The result is that the front wheels no longer have a steady contact with the road. Active damping can modulate the linkage position to offset these oscillations. Normally, the draft sensors sense these oscillations and provide the input signal to the control.

**Front hitch active damping**

Active damping can benefit a front hitch as well as the rear hitch. You can add pressure sensors to the system to provide the necessary signals to the hitch control application block.

## System Description      Hitch Control

### Control options


#### Overview

Control for single and double acting hitch control systems are combined in one software application block. This allows users to select the appropriate valve for the system. Options include single acting, double acting, and switchable (between single and double acting).

#### PVBZ double-acting actuator control

The PVBZ meets basic market requirements for front hitches and auxiliary valves, that raise and lower implements hydraulically. This includes the float feature.


*Typical double-acting system used for front hitch*



#### PVBZ-HS single-acting actuator control

The PVBZ-HS meets market requirements for single-acting rear hitches, that raise implements hydraulically and lower them by gravity.

*Typical single-acting system used for rear hitch*





## System Description      Hitch Control


### Control options

#### PVBZ-HD single and double-acting actuator control

The PVBZ-HD is a more advanced alternative to the PVBZ or PVBZ-HS. This valve can operate either as double-acting or single-acting.

The PVBZ-HD has the ability to raise, lower, press down, or float. In double-acting mode, the PVBZ-HD increases comfort and safety when attaching and detaching heavy implements because of its ability to raise and lower at the same speed. For field operation you may select either single or double-acting mode.

*Advanced hitch system: Capable of switching between double or single-acting*



3516

---

<b>System Description</b>	<b>Hitch Control</b>
---------------------------	----------------------

---

## Hardware components

### Hitch valves

The valve options for the Danfoss hitch control system include PVBZ double-acting, PVBZ-HS single-acting, and the PVBZ-HD single and double-acting valves. These proven PVG 32 valves feature pressure compensation, low leakage ports (P/O-check), and optional PVLP shock/anticavitation valves. These features are contained in PLUS+1® Compliant valve sections that incorporate ISO bus compatible PVED electrical actuation, making them easy to integrate into the vehicle hydraulic system.

### Sensors

Following is a summary of typical sensors and recommended suppliers:

#### **Draft sensors for force control**

Vendors: Bosch Rexroth, Vishay

Sensor excitation voltage requirements must be compatible with the selected PLUS+1® microcontroller power supply rating.

#### **Angle sensor for displacement control**

Vendor: Honeywell

RPN Series Rotary Position Sensors use a magnetically biased Hall effect integrated circuit to accurately sense rotary movement of the actuator shaft.

#### **Ground speed radar**

Vendor: Dickey-john

The Dickey-john RVSIII series Radar Velocity Sensors utilize Doppler radar technology to output a signal that is proportional to ground speed.

### Microcontrollers

A wide range of keyed PLUS+1® microcontrollers are available, including 24 pin, 50 pin, and 88 pin models.

#### **PLUS+1® controller power supply specification**

Normal sensor power supply output specification for Danfoss microcontrollers is 5 Vdc. Output current rating ranges from 200 mA to 500 mA depending on the microcontroller model you select for your application. Please refer to individual microcontroller data sheets for additional details.

#### **MC024-01A controller for 10 Vdc draft sensors**

The MC024-01A is an element of the PLUS+1® family of mobile machine management products. It is a keyed general-purpose controller equally suited for use in a distributed machine control system, or as a stand-alone controller.

This controller has a 10 Vdc, 0.5 A sensor supply output for use with existing hitch sensors on the market requiring a 10 Vdc power supply.

#### **HWD for PLUS+1® controllers**

Danfoss provides hardware description files (\*.HWD file) for PLUS+1® microcontrollers. Each .HWD file includes the operating system software for a particular microcontroller. Select a microcontroller with input/output and power supply specifications that is suitable for your application.

---

<b>System Description</b>	<b>Hitch Control</b>
---------------------------	----------------------

---

## Application software

### Application block software description

The hitch control application block is a graphical representation of software algorithms that provide the foundation for automated hitch control. Specific tailoring of the block is accomplished using Danfoss PLUS+1® GUIDE tool set. GUIDE allows developers to build application software for use with Danfoss PLUS+1® controllers. The PLUS+1® Service Tool is used to download the compiled application to the target microcontroller.

### PLUS+1® GUIDE

Customers use the hitch control application block as the starting point for a complete hitch system application that includes input mapping, calibration, fault handling, output mapping, and connection for HMI devices and microcontroller outputs.

The application block is released as a .SCS file, which means it can be dragged onto the GUIDE programming workspace to be included as the application block for a complete, user-developed hitch system application.

### PLUS+1® Service Tool

The PLUS+1® Service Tool is included with the PLUS+1® GUIDE user license.

#### PLUS+1® Service Tool functions

- Downloads software to keyed PLUS+1® hardware
- Transfers data from the microcontroller to a PC
- Provides interface for developing service screens for machine diagnostics, setup, and tuning

#### Keyed PLUS+1® application block software and application hardware

If the application hardware key matches the application software key 10106603 the service tool permits the download to the target application hardware.

### Customer access to the Hitch application block

The Hitch Control Application File, 70024823.ZIP

#### Application file contents

Software and documents enclosed in the application file include:

- Hitch Control Application Block, 10108138 (\*.SCS)
- *Hitch Control Application Block User Manual, 11033753* (\*.PDF)
- *Hitch Control System Description, 11036124* (\*.PDF)

#### Application file download and installation in GUIDE

After downloading the application file to your hard drive, you can install the application block code in the My Blocks tab of the GUIDE component selector menu, for easy access during application development.

Software user manual and other technical information documents from the application file may be stored in any convenient folder on your hard drive.

---

<b>System Description</b>	<b>Hitch Control</b>
---------------------------	----------------------

---

## Features and benefits

### Standard features

- Single-acting and double-acting proportional valves as well as advanced multi-function valve that can switch between single and double-acting
- Available PLUS+1® microcontroller with a 10 Vdc sensor supply voltage suitable for general market draft sensors
- Wide range of standard PLUS+1® microcontrollers with 5 Vdc sensor power supply
- Available I/O extension modules for the microcontroller to accommodate a larger number of analog signals from the HMI, if needed
- A generic, user-programmable application block software for controlling the hitch position

### Optional features

Other hitch control components, such as HMI controls and sensors, are typically OEM-specific, and are not part of the Danfoss standard hitch control portfolio at this time. However, Danfoss can work with customers to develop custom OEM-specific interface solutions.

In addition, Danfoss can assist with development of complete software solutions, tailored to specific requirements of the OEM interface and HMI specifications, based on the application block that is described in this document.

### Benefits

- Application block software is GUIDE programmable by end user: A complete software solution can be created by extending the application block provided by Danfoss
- Faster and easier prototyping, set-up and tuning
- Simple logics—better user understanding
- Single or double acting system in one software application
- Double acting operation features enables higher safety and comfort
- Precise control and repeatability
- Simplified control of displacement force and slip factors
- Safer attachment and removal of implements
- Stable, closed-loop control in all operating modes

---

**System Description****Hitch Control**

---

---

**System Description****Hitch Control**

---

---

**System Description****Hitch Control**

---



**Products we offer:**

- Bent Axis Motors
- Closed Circuit Axial Piston Pumps and Motors
- Displays
- Electrohydraulic Power Steering
- Electrohydraulics
- Hydraulic Power Steering
- Integrated Systems
- Joysticks and Control Handles
- Microcontrollers and Software
- Open Circuit Axial Piston Pumps
- Orbital Motors
- PLUS+1® GUIDE
- Proportional Valves
- Sensors
- Steering
- Transit Mixer Drives

**Danfoss Power Solutions** is a global manufacturer and supplier of high-quality hydraulic and electronic components. We specialize in providing state-of-the-art technology and solutions that excel in the harsh operating conditions of the mobile off-highway market. Building on our extensive applications expertise, we work closely with our customers to ensure exceptional performance for a broad range of off-highway vehicles.

We help OEMs around the world speed up system development, reduce costs and bring vehicles to market faster.

Danfoss – Your Strongest Partner in Mobile Hydraulics.

**Go to [www.powersolutions.danfoss.com](http://www.powersolutions.danfoss.com) for further product information.**

Wherever off-highway vehicles are at work, so is Danfoss. We offer expert worldwide support for our customers, ensuring the best possible solutions for outstanding performance. And with an extensive network of Global Service Partners, we also provide comprehensive global service for all of our components.

Please contact the Danfoss Power Solution representative nearest you.

**Comatrol**

[www.comatrol.com](http://www.comatrol.com)

**Schwarzmüller-Inverter**

[www.schwarzmueller-inverter.com](http://www.schwarzmueller-inverter.com)

**Turolla**

[www.turollaocg.com](http://www.turollaocg.com)

**Hydro-Gear**

[www.hydro-gear.com](http://www.hydro-gear.com)

**Daikin-Sauer-Danfoss**

[www.daikin-sauer-danfoss.com](http://www.daikin-sauer-danfoss.com)

Local address:

**Danfoss Power Solutions (US) Company**  
2800 East 13th Street  
Ames, IA 50010, USA  
Phone: +1 515 239 6000

**Danfoss Power Solutions GmbH & Co. OHG**  
Krokamp 35  
D-24539 Neumünster, Germany  
Phone: +49 4321 871 0

**Danfoss Power Solutions ApS**  
Nordborgvej 81  
DK-6430 Nordborg, Denmark  
Phone: +45 7488 2222

**Danfoss Power Solutions Trading (Shanghai) Co., Ltd.**  
Building #22, No. 1000 Jin Hai Rd  
Jin Qiao, Pudong New District  
Shanghai, China 201206  
Phone: +86 21 3418 5200

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.